

По вопросам продаж и поддержки обращайтесь:

Архангельск +7 (8182) 45-71-35
Астрахань +7 (8512) 99-46-80
Астана +7 (7172) 69-68-15
Барнаул +7 (3852) 37-96-76
Белгород +7 (4722) 20-58-80
Брянск +7 (4832) 32-17-25
Владивосток +7 (4232) 49-26-85
Владимир +7 (4922) 49-51-33
Волгоград +7 (8442) 45-94-42
Воронеж +7 (4732) 12-26-70
Екатеринбург +7 (343) 302-14-75
Иваново +7 (4932) 70-02-95
Иркутск +7 (3952) 56-24-09
Иошкар-Ола +7 (8362) 38-66-61
Ижевск +7 (3412) 20-90-75
Казань +7 (843) 207-19-05

Курск +7 (4712) 23-80-45
Липецк +7 (4742) 20-01-75
Магнитогорск +7 (3519) 51-02-81
Москва +7 (499) 404-24-72
Мурманск +7 (8152) 65-52-70
Набережные Челны +7 (8552) 91-01-32
Нижний Новгород +7 (831) 200-34-65
Нижевартонск +7 (3466) 48-22-23
Нижнекамск +7 (8555) 24-47-85
Новосибирск +7 (383) 235-95-48
Калуга +7 (4842) 33-35-03
Калининград +7 (4012) 72-21-36
Кемерово +7 (3842) 21-56-70
Киров +7 (8332) 20-58-70
Краснодар +7 (861) 238-86-59
Новороссийск +7 (8617) 30-82-64

Омск +7 (381) 299-16-70
Орел +7 (4862) 22-23-86
Оренбург +7 (3532) 48-64-35
Пенза +7 (8412) 23-52-98
Пермь +7 (342) 233-81-65
Первоуральск +7 (3439) 26-01-18
Ростов-на-Дону +7 (863) 309-14-65
Рязань +7 (4912) 77-61-95
Самара +7 (846) 219-28-25
Санкт-Петербург +7 (812) 660-57-09
Саратов +7 (845) 239-86-35
Саранск +7 (8342) 22-95-16
Сочи +7 (862) 279-22-65
Ставрополь +7 (8652) 57-76-63
Сургут +7 (3462) 77-96-35
Смоленск +7 (4812) 51-55-32

Сызрань +7 (8464) 33-50-64
Сыктывкар +7 (8212) 28-83-02
Тверь +7 (4822) 39-50-56
Томск +7 (3822) 48-95-05
Тула +7 (4872) 44-05-30
Тюмень +7 (3452) 56-94-75
Ульяновск +7 (8422) 42-51-95
Уфа +7 (347) 258-82-65
Хабаровск +7 (421) 292-95-69
Челябинск +7 (351) 277-89-65
Чебоксары +7 (8352) 28-50-89
Череповец +7 (8202) 49-07-18
Ярославль +7 (4852) 67-02-35

сайт: promag.pro-solution.ru | эл. почта: ehr@pro-solution.ru

телефон: **8-800-511-8870**

Россия, Казахстан и другие страны ТС доставка в любой город

Endress Hauser Analog chlorine dioxide sensor CCS50



CCS50 is a robust, low-maintenance sensor for chlorine dioxide measurement. It provides stable and fast measured values in water, process water and utilities. The sensor ensures efficient disinfection even at minimum water volumes and helps to achieve highest water quality and safety, to avoid overdosing of chlorine dioxide or to ensure the absence of ClO₂ in beverage plants and reverse osmosis. CCS50 ensures continuity for the installed base of analog chlorine dioxide measuring points.

Применение

Drinking water - to ensure reliable disinfection

Cooling water - to avoid biofilm growth

Food - to ensure food quality

Utilities to secure the absence/presence of chlorine dioxide

Характеристики

Amperometric measurement of dissolved chlorine dioxide

Диапазон измерения

Trace: 0 to 5 mg/l ClO₂

Standard: 0 to 20 mg/l ClO₂

Measuring method

- Closed, membrane covered measuring cell
- Reduction of chlordioxide at the cathode

Конструкция

Closed amperometric 2-electrode measuring cell with PVDF membrane

Материал

Sensor shaft: PVC

Membrane: PVDF

Membrane cap: PVDF

Габаритные размеры

Diameter: 25 mm (0.98 in)

Length: 161 mm (6.34 in)

Рабочая температура

+0 to 55 °C (32 to 130°F), non-freezing

Рабочее давление

1 bar (14.5 psi)

Датчик температуры

10k NTC

Подключение

analog with fixed cable

Характеристики

Бренд: Endress